



d-COLOR P3100

PERFORMANCE WITH STYLE IN THE OFFICE

STYLE AND QUALITY FOR A COMPACT SPACE

The **d-Color P3100** is the perfect solution for users who want their printer to provide quality as well as functionality. Quality reflected in a smart, compact design, superior colour printing, paper capacity of up to 850 sheets (250 sheets in the standard tray, 500 sheets in the optional tray, 100 sheets in the By-Pass).

Compact and lightweight, the **d-Color P3100** printer has a stylish, sophisticated design. Easy to use, fast and functional, this printer is intended for advanced professional users and complex workgroups, guaranteeing excellent printing quality and low energy consumption.

HIGH PERFORMANCE

The **d-Color P3100** is not just superior printing quality, but also high printing speed. It delivers up to 31 A4 colour pages per minute, with the first page out in just 12.9 seconds. The standard automatic duplex function (A4) guarantees a reduction in paper consumption and archive space, while the USB host port and 4-line LCD display make it possible to print directly from memory sticks with the optional HDD installed.

STYLE THAT CARES FOR THE ENVIRONMENT

Perfect print-outs in next to no time with full respect for the environment. The **d-Color P3100** minimises use of energy and paper, providing savings for the user and keeping a close eye on the environment (Blue Angel and Energy Star 2.0 compliant).

PRINTING SPEED: UP TO 31 PPM, IN COLOUR AND MONO, IN A6-A4 AND CUSTOMISED FORMATS

4-LINE LCD DISPLAY

STANDARD DUPLEX (A4)

USB PORT FOR DIRECT PRINTING FROM MEMORY STICKS⁺

STANDARD MEMORY UP TO 1 GB, EXPANDABLE TO 2 GB

OPTIONAL IC CARD READER⁺

⁺ requires optional 320 GB Hard Disk




COLOUR



SPEED



COMPACT



NETWORK



ECONOMICAL



LOW NOISE



Optional



QUALITY



WI FI



COLOUR LASER PRINTER



Professional A4 colour printer with stylish design



4-line LCD operator panel



3 input paper trays (optional)

TECHNICAL SPECIFICATIONS

PRINTER

Technology	Laser, A4 colour
Printing Speed	Up to 31 ppm
First Print Out Time	12.9 sec.
Warm-up Time	36 sec.
Processor	PPC 1,066 GHz (MV78230)
Std./Max. Memory	1 GB/2 GB (optional)
Resolution	1200 x 1200 dpi
Display	LCD 4 lines (160 x 64 mono full-dot backlight)
Standard Interfaces	USB 2.0, USB Host 2.0, Ethernet NIC10Base-T/100Base-TX/1000Base-T
Emulations	PCL5 e/c, PCL XL Version 3.0, PostScript 3, XPS Version 1.0 (with HDD installed), PPML/GA.2.2 (with HDD installed), PPML VDX (with HDD installed), OpenXPS (with HDD installed), PDF 1.7 (with HDD installed)
Operating Systems	All current Windows OS (incl. Win7 32/64 and Win 8 32(64), Mac Os X version 10.8.2 or higher, Unix, Linux, Citrix
Fonts	80 scalable (PCL Latin) accessible in all emulations, 137 PostScript 3

PAPER MANAGEMENT

Standard Tray	250 sheets; A6-A4; 60-210 g/m ²
Optional Paper Tray	1 x 500 sheets; A4; 60-90 g/m ²
Max. Paper Capacity with options	850 sheets
Duplex	Standard, 60-210 g/m ² A4, B5, Legal, Letter
Paper Output Tray Capacity	Max. 200 sheets
By-Pass	100 sheets; A6-A4, Custom, 60-210 g/m ²

GENERAL

TEC (kWh/week)	2.1
Noise Level	In print mode: < 54 dB(A) LpA
Energy Consumption	Max. consumption: <1.2 kW Print mode: 640 W Standby: 130 W Sleep mode: 3 W or less
Power Requirement	220-240 V, 50/60 Hz
Dimensions (W x D x H)	447 x 544 x 350 mm
Weight (kg)	23.5 kg (main body only)
Toner Consumables	Toner cartridge (C,M,Y,K): Cyan, Magenta, Yellow & Black toner capacity up to 5,000 A4 pages; Starter toner capacity up to 4,700 A4 pages

OPTIONS

Paper Tray (PF-P14)	500 sheets (up to 90 g/m ²) A4
Copy Stand (SCD-25)	To place the printer at the correct operational height / storage
320GB HDD (HD-P06)	Enables the following functionality: - Electronic Sorting - Job Control / Job Deletion - Proof & Print / Secure Print - Direct Print / Print from USB - Licence Kit Support / IC Card Reader Support
Memory Expansion	1 GB (for faster processing)
Wireless LAN Connector	SX-BR-4600
RFID - Card Reader	IC Card Reader
Barcode Font (LK-106)	Support for Barcode printing
Unicode Font (LK-107)	Support for Unicode printing
OCR A and B Fonts (LK-108)	Support for OCR A and B printing
ThinPrint (LK-111)	Native ThinPrint Client

Product performances are referred to as appropriate use under optimal conditions. The registered trademarks are the property of their respective owners.

The support and availability of the listed specifications and functionalities varies depending upon operating systems, applications, network protocols as well as network and system configurations. All information relating to specification and accessories is subject to change without notice. Olivetti does not guarantee that any prices or specifications mentioned will be error-free. The d-Color P3100 is distributed by Olivetti S.p.A. (09/14) - Code: 29315-00

OLIVETTI UK LIMITED.
500 AVEBURY BOULEVARD
MILTON KEYNES, MK9 2BE
WWW.OLIVETTIUK.COM

